



RFI 230 2GZ USP

TRAVERSA IN C.A.P. PER GIUNZIONI
CONCRETE SLEEPER FOR JOINTS



- Conformi alle norme EN 13230-1/2 ed alle
- Specifiche Tecniche RFI
- Lunghezza: 2300 mm
- Larghezza: 400 mm
- Altezza sottorotaia: 167,5 mm
- Massa: 333 kg
- $M_{dr} \geq +12,5$ kNm momento di flessione positivo di progetto per la sezione sottorotaia
- $M_{dcn} \geq -16,5$ kNm momento di flessione negativo di progetto per la sezione di mezzzeria
- $M_{dc} \geq +11,5$ kNm momento di flessione positivo di progetto per la sezione di mezzzeria
- USP: Materassino Sotto Traversa conforme alle
- Specifiche Tecniche RFI TCAR SF AR 03 008

- In accordance with EN 13230-1/2 and Technical Specification RFI
- Length: 2300 mm
- Width: 400 mm
- Depth at rail seat 167,5 mm
- Mass: 333 kg
- $M_{dr} \geq +12,5$ kNm positive design bending moment at rail seat
- $M_{dcn} \geq -16,5$ kNm negative design bending moment at center
- $M_{dc} \geq +11,5$ kNm positive design bending moment at center
- USP: Under Sleeper Pad in accordance with Technical Specification RFI TCAR SF AR 03 008