


# RFI 230 VN

TRAVERSA IN C.A.P. PER LINEE TRADIZIONALI (VELOCITÀ  $\leq 250$  km/h)

CONCRETE SLEEPER FOR TRADITIONAL LINES (SPEED  $\leq 250$  km/h)



- Conforme alle norme EN 13230-1/2 ed alle Specifiche Tecniche RFI TCAR SF AR 03 002
- Lunghezza: 2300 mm
- Larghezza: 300 mm
- Altezza sottorotaia: 182 mm
- Massa: 248 kg
- $M_{dr} \geq +12,5$  kNm momento di flessione positivo di progetto per la sezione sottorotaia
- $M_{dcn} \geq -10,5$  kNm momento di flessione negativo di progetto per la sezione di mezzeria
- $M_{dc} \geq +7,5$  kNm momento di flessione positivo di progetto per la sezione di mezzeria
- Disponibili anche con USP conformemente alle Specifiche Tecniche RFI TCAR SF AR 03 008

- *In accordance with EN 13230-1/2 and Technical Specification RFI TCAR SF AR 03 002*
- *Length: 2300 mm*
- *Width: 300 mm*
- *Depth at rail seat: 182 mm*
- *Mass: 248 kg*
- *$M_{dr} \geq +12,5$  kNm positive design bending moment at rail seat*
- *$M_{dcn} \geq -10,5$  kNm negative design bending moment at center*
- *$M_{dc} \geq +7,5$  kNm positive design bending moment at center*
- *Available with USP in accordance with Technical Specification RFI TCAR SF AR 03 008*